



Features :

- Interface USB + LAN
- Equipped dual motor
- Supporting TSPL-EZ printer language
- Large visual windows
- Print speed up to 127mm/s



Retail



Take Away



Manufacturing

Specification



Brand	xLab
Product Name	xLab XBLP-426T Thermal Barcode Label & POS Printer
Model	XBLP-426T
Print Method	Thermal Transfer / Direct Thermal
Print Speed	127 mm/s Max
Resolution	203 DPI
Print Width	104 mm (4.09")
Max Print Length	1778 mm (70")
Processor	32-bit CPU
RAM	8MB SDRAM
Flash	8MB, Expandable up to 4GB
Interface	USB + LAN
Ribbon Capacity	Max. 300m
Ribbon Width	110 mm
Ribbon Core Diameter	25.4 mm (1")
Media Width	25.4-118 mm (1"-4.6")
Media Thickness	0.06-0.254 mm
Media Core Diameter	25.4-76.2 mm (1"-3")
Label Roll Capacity	127 mm (5") OD
Label Length	10-1778 mm (0.39"-70")
Media Types	Continuous, Gap, Black Mark, Fan-Fold, Punched Hole
Sensors	Gap, Cover Opening, Black Mark, Ribbon Sensor
Print Head Life	30 km
Internal Fonts	8 Alpha-Numeric Bitmap Fonts; Windows Fonts Downloadable
Rotation	0°, 90°, 180°, 270°
1D Barcodes	Code 39, Code 93, Code 128, Codabar, Interleaved 2 of 5, EAN-8, EAN-13, EAN-128, UPC-A, UPC-E, MSI, Plessey, POSTNET, China Post
2D Barcodes	PDF-417, MaxiCode, Data Matrix, QR Code, Aztec
Emulation	TSPL, EPL, ZPL, DPL
Factory Options	Ethernet, RS-232C, Cutter, Peeling Machine, Bluetooth Module, Wi-Fi Module
Optional Interfaces	Serial, LAN, Wi-Fi, Bluetooth
Operating Temperature	5-40°C
Operating Humidity	25-85% RH, Non-condensing
Storage Temperature	-40-60°C
Storage Humidity	10-90% RH, Non-condensing
Driver	Windows, Linux, Mac
Dimensions	299 × 235 × 198.3 mm (D × W × H)
Product Weight	2.55 kg